

I-12 MODEL No.

Description

TPS4540

Plain Steel .134" (3.4)mm
Full Mortise Spring Hinge
Commercial Grade
4.5"(114.3) x 4.0"(101.6)

- Steel base material
- Meets NFPA 80 for 3 hour fire doors (minimum 2 per door)
- Template screw hole locations to speed installation
- Maximum door weight 130 lbs (59)kg
- Max door size 3' x 7'6" (914 x 2286)mm (2 hinges per door)
- Conforms to ANSI K81071F
- Available in USP, 3, 4, 10, 10A, 26, 26D



TPS4545

Plain Steel .134" (3.4)mm
Full Mortise Spring Hinge
Commercial Grade
4.5"(114.3) x 4.5"(114.3)

- Steel base material
- Meets NFPA 80 for 3 hour fire doors (minimum 2 per door)
- Template screw hole locations to speed installation
- Maximum door weight 180 lbs (82)kg
- Max door size 3' x 7'6" (914 x 2286)mm (3 hinges per door)
- Conforms to ANSI K81071F
- Available in USP, 3, 4, 10, 10A, 26, 26D





MODEL No.	Description	I-13
-----------	-------------	------

TSS4540

Stainless Steel .134" (3.4)mm
 Full Mortise Spring Hinge
 Commercial Grade
 4.5"(114.3) x 4.5"(101.6)

- Stainless steel base material
- Meets NFPA 80 for 3 hour fire doors (minimum 2 per door)
- Template screw hole locations to speed installation
- Maximum door weight 130 lbs (59)kg
- Max door size 3' x 7'6" (914 x 2286)mm (2 hinges per door)
- Conforms to ANSI K51071F
- Available in US32, 32D



TSS4545

Stainless Steel .134" (3.4)mm
 Full Mortise Spring Hinge
 Commercial Grade
 4.5"(114.3) x 4.5"(114.3)

- Stainless steel base material
- Meets NFPA 80 for 3 hour fire doors (minimum 2 per door)
- Template screw hole locations to speed installation
- Maximum door weight 180 lbs (82)kg
- Max door size 3' x 7'6" (914 x 2286)mm (3 hinges per door)
- Conforms to ANSI K51071F
- Available in US32, 32D

